

Advanced IP Phone with 3 lines & HD voice

- TI TITAN chipset and TI voice engine
- 3 VoIP accounts, 132x64 graphic LCD
- HD Voice: HD Codec, HD speaker, HD handset
- IPV6, BLF, XML Browser, Hot-desking, OpenVPN
- 6 DSS keys, 2xLAN, PoE, Headset, Expansion module



SIP-T65 is designed for maximum productivity and efficiency in the everyday business environment. Equipped with the TI TITAN chipset, SIP-T65 offers high definition voice quality through TI voice engine, HD handset, HD speaker and HD codec (G.722). It offers 3 VoIP accounts, built in 6 DSS keys for programmed as the IP-PBX features like BLF/BLA, call park, call pickup, call recording etc. The 132x64 graphic LCD, 4 soft keys and 4-way navigation keys helps using the phone easily. Moreover, T65 has the rich external interfaces including 2xLAN, PoE, headset and expansion module ports.

Phone Features

3 VoIP accounts, Hotline, Emergency call
 Call hold, Call waiting, Call forward, Call return
 Call transfer (blind/semi-attended/attended)
 Caller ID display, Redial, Mute, DND
 Auto-answer, 3-way conferencing
 Speed dial, SMS, Voicemail
 Message Waiting Indication (MWI) LED
 Tone scheme, Volume control
 Direct IP call without SIP proxy
 Ring tone selection/import/delete
 Phonebook (300 entries), Black list
 Call history: dialed/received/missed/forwarded
 Menu-driven user interface
 Localized language and input method
 Hard keys programmable at idle status
 Soft keys programmable
 Supports up to 6 expansion modules(CM68/CM69)
 Supports Wireless Headset Adapter(EHS36)

Advanced Features

XML phonebook search/import
 LDAP phonebook,PUSH XML
 XML Browser, Hot-desking
 Action URL & Active URI
 Headset (Call center mode)
 Multicast IP Paging

IP PBX System Integration

Busy lamp field (BLF),BLF list
 Bridged line appearance (BLA)
 DND&Forward synchronization
 Intercom, Paging, Music on hold
 Call park, Call pickup
 Call recording, Call completion
 Group listening, Group pickup
 Anonymous call, Anonymous call rejection
 Network conference
 Distinctive ringtone
 Dial Plan, Dial-now

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS
 Auto-provision with PnP
 SNMP V1/2 , TR069 optional
 Configuration: browser/phone/auto-provision
 Factory configuration customized
 Trace package and system log export

Security

Open VPN, 802.1x, VLAN QoS (802.1pq)
 Transport Layer Security (TLS)
 HTTPS (server/client), SRTP (RFC3711)
 Digest authentication using MD5/MD5-sess
 Secure configuration file via AES encryption
 Phone lock for personal privacy protection
 Admin/VAR/User 3-level configuration mode

Codecs and Voice Features

Wideband codec: G.722
 Narrowband codec: G.711μ/A, G.723.1
 G.726, G.729AB
 VAD, CNG, AEC, PLC, AJB, AGC
 Full-duplex speakerphone with AEC

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
 IPV6
 DNS SRV (RFC3263)
 Redundant server support
 NAT Traversal: STUN mode
 DTMF: In-Band, RFC2833, SIP Info
 Proxy mode and peer-to-peer SIP link mode
 IP Assignment: Static/DHCP/PPPoE
 Bridge/router mode for PC port
 TFTP/DHCP/PPPoE client
 Telnet/HTTP/HTTPS server
 DNS client, NAT/DHCP server
 Logout

Physical Features

TI TITAN chipset
 132x64 graphic LCD with backlight
 39 keys including 11 function keys
 6xDSS keys each with a dual-color LED
 9 LEDs: 6xDSS keys, 1xpower, 1xmessage
 1xheadset
 1xRJ9 (4P4C) handset port
 1xRJ9 (4P4C) headset port
 2xRJ45 10/100M Ethernet ports
 1XRJ12 (6P6C) EXT port
 Power adapter: AC 100~240V input and
 DC 5V/1.2A output
 Detachable foot stand, Wall-mountable
 Power over Ethernet (IEEE 802.3af)
 Power consumption: 1.6-2.6W
 Net weight: 0.77kg
 Dimension: 265 x 128 x 210mm
 Operating humidity: 10~95%
 Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS
 N.W/CTN: 7.553KG
 G.W/CTN: 10.703KG
 Measurement: 0.051CMB
 Carton Meas: 665 x 545 x 220MM

Certifications

